

# ASSEMBLY AND INSTALLATION INSTRUCTION

**WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!**

NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.

## Installation Steps:

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Outlet Box. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
2. Assemble the threaded nipple onto the cross bar and lock it in place with a hex nut. Attach the cross bar to outlet box by using two outlet box screws upwards. The side of the mounting plate marked "GND" must face to out.
3. **See Fig.1.** Place the arcuation frame at the center of the lamp body, aligning the top square salient point and bottom indentation, lock it securely with the mounting screws. Feed the wires from lamp holder through pipes and lamp body 's center thread pipe, thread the threaded nipple to inside of pipe, connect all the parts together until secure.
4. **See Fig.2 and Fig.3.** Attach the silica gel strips into arcuation face, then place the glass shade onto the arcuation in the lamp body frame.
5. **See Fig.4.** Feed the wires from lamp body through the threaded pipe and fixture loop, by turn it clockwise until tighten.
6. Determine the length of chain needed, using pliers to disconnect the unneeded chain. Connect desired chain length using chain links. Put one chain link on the fixture loop and the other one on screw collar.
7. Weave the fixture wires including ground wire through fixture loop, every other chain, screw collar, collar ring, canopy, and threaded nipple on the cross bar. Secure the screw collar onto the threaded nipple.
8. **Make wire connections:**  
 --attach fixture ground wire to supply ground wire using a wire nut or attach them to the mounting plate with a green ground screw.  
 --attach white wire from light to white wire from power source with a wire nut.  
 --attach black wire from light to black wire from power source with a wire nut.  
**Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.**  
**\*\*\*Make sure all wire connectors are secured and do not easily pull off with the slight tug.**
9. Once all wires are connected, tuck them carefully into outlet box. Attach the canopy to the ceiling then thread the collar ring on screw collar to secure the canopy.
10. Install bulbs. (not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
11. Your installation is now complete. Return the power to the outlet box and test the fixture.

